



uPVC Window & Door Order Form

Unit 4, Yarrow Mill
Yarrow Road
Chorley. PR6 0LP

Customer Name & Address:	Delivery address if different:	Customer Ref:
		Customer Order No:
Contact:		Date Required:
Tel:		

Profile	Outer Frame Size	Colour	WER Rating	Glazing
Sculptured (std.)	70mm (Std)	External:	A+	B Supply Glass
Bevelled	55mm	Internal:	A (std)	C Supply Panel

All overall sizes include any cills & add-ons. All frames are viewed from the outside

Sketch		Dimensions overall frame size	Add-Ons 15, 25 & 40mm	Cills	Window Extras	Door Details	Door Extras	Glass/Panel details:	
QTY	Location								
		FRAME WIDTH	TOP	None – Face Drain	Trickle Vents – Show details on the sketch	Opening			
						In	Out		55mm Bottom Rail
		FRAME HEIGHT	BOTTOM	None – Concealed Drain	Easy Clean Espag Hinges	Hinged or Master door on the:			Stormguard low thresher
						Left	Right		Restrictor (Open out only)
TRANSOM DROP	LEFT	95mm	Restricted Hinges	Midrail height:		Letterplate			
		150mm		(Std – 850mm)					
SASH WIDTH	RIGHT	180mm	Non-locking handle			Knocker			
		250mm							

Hardware Colour:

Sketch		Dimensions overall frame size	Add-Ons 15, 25 & 40mm	Cills	Window Extras	Door Details	Door Extras	Glass/Panel details:	
QTY	Location								
		FRAME WIDTH	TOP	None – Face Drain	Trickle Vents – Show details on the sketch	Opening			
						In	Out		55mm Bottom Rail
		FRAME HEIGHT	BOTTOM	None – Concealed Drain	Easy Clean Espag Hinges	Hinged or Master door on the:			Stormguard low thresher
						Left	Right		Restrictor (Open out only)
TRANSOM DROP	LEFT	95mm	Restricted Hinges	Midrail height:		Letterplate			
		150mm		(Std – 850mm)					
SASH WIDTH	RIGHT	180mm	Non-locking handle			Knocker			
		250mm							

Hardware Colour:

Sketch		Dimensions overall frame size	Add-Ons 15, 25 & 40mm	Cills	Window Extras	Door Details	Door Extras	Glass/Panel details:	
QTY	Location								
		FRAME WIDTH	TOP	None – Face Drain	Trickle Vents – Show details on the sketch	Opening			
						In	Out		55mm Bottom Rail
		FRAME HEIGHT	BOTTOM	None – Concealed Drain	Easy Clean Espag Hinges	Hinged or Master door on the:			Stormguard low thresher
						Left	Right		Restrictor (Open out only)
TRANSOM DROP	LEFT	95mm	Restricted Hinges	Midrail height:		Letterplate			
		150mm		(Std – 850mm)					
SASH WIDTH	RIGHT	180mm	Non-locking handle			Knocker			
		250mm							

Hardware Colour:

GENERAL NOTES:

Please process this order. I accept the terms & conditions of sale. Signed: _____ Date: _____ Page _____ of _____

Please note the we can only accept written notification of any cancellations or alterations to this order. A cost may be incurred if any cancellations or alterations are made. It is the responsibility of the person ordering to ensure all designs & specifications comply with current legislation.

CJM Lancashire Ltd. Specification

Default Specification

Where information is missing we assume the items are to be made to our standard specification;

Outerframe will be the 70mm Deceuninck 2800 sculptured system. Transom drop is 400mm and the mullion split will be equal if the frame is under 1450mm wide with wider frames having a mullion split of 600mm if a sash is specified. The frames will have concealed drainage and supplied with a 150mm cill. Standard glazing is 28mm double glazed unit, clear glass, Low 'E' on the inside pane, argon filled cavity and warm edge spacer bar. Standard midrail height is 850mm excluding cill. All frames and sashed will be reinforced as necessary.

Trickle vents, if specified, will be placed in any sashes, if there is a sash over a sash the top sash will receive the trickle vent. Unless specified, the maximum physical size of trickle vent will be used.

Size restrictions

Casement Windows	Min Width	Min Height	Max Width	Max Height
Fixed light	230mm	230mm	2000mm	2000mm
Top Hung Sash	230mm	275mm	1150mm	1150mm
Side Hung	275mm	230mm	650mm*	1350mm
Tilt & Turn Windows & Doors				
Tilt & Turn Sash	320mm	360mm	1415mm	1415mm
Single Door Sash	600mm	1850mm	915mm	2090mm
Double Door Sash	600mm	1850mm	915mm	2090mm

*850mm can be manufactured with heavy duty hinge at an additional cost.

We can make sash's larger than what is specified above however we will not guarantee the performance of any other-sized items.

'A' RATING

As standard we offer an 'A' Rated 70mm windows as standard when we supply the double glazed units. The double glazed units feature a warm-edge spacer bar, argon gas filling and a high performance soft-coat Low 'E' internal pane.

Single and double doors, tilt & turn windows and double glazed units with an aluminium spacer bar will not meet the 'A' rating criteria. We are registered with the Thermal Rating Register and certificates for our windows can be found on their website.